PARK VALENCIA ALZIRA



Park Valencia Alzira offers up to 65,000 sq m of industrial space suitable for production and logistic activities. In an excellent location south of Valencia, with direct access to A7 highway, and within 25 minutes from the city of Valencia and the harbor.



VALENCIA 40 km, 39 min **BARCELONA** 397 km, 240 min



LOCATION IS KEY

DEVELOPMENT SPACE

Park Valencia Alzira offers 65,000 sq m of industrial space suitable for logistic and production activities.

ACCESS


Perfect accessibility - direct access to A7 highway, and within 25 minutes from the city of Valencia and the harbor

LABOR FORCE

Qualified labor force available from nearby cities as Valencia and Alicante.

PUBLIC TRANSPORT

A bus stop is located nearby the park. A train stop is also available in its vicinity.




BUILDING INFORMATION

Building 1

65,000 sq m

WAREHOUSE

Structure grid 12 m × 24 m Clear height 11 m Slab load (punctual VS M2) Load flatness level FM2 FF45 FL35 Lighting type LED/BMS & 4% natural light Power supply 35 W/m²



OFFICE PREMISES

Clear height 2.7 m Light intensity 500 lux Built to suit solution

SUSTAINABILITY TREND

We meet the strictest standards of modern, environmentally friendly construction.

This is why our projects aim for the BREEAM "Excellent" rating at least.



STANDARD TECHNICAL SPECIFICATION

1 SUPPORTING STRUCTURE

Pad or pilot foundations, insulated plinth panels up to 30 cm above floor.

6 HALL INSTALLATIONS

Gas Sahara heaters or infrared gas radiators, heating according to norms for warehousing

Fibre reinforced concrete floor, PE membrane, cut joints, 1st floor 20 cm thick, 2nd-4th floor 12 cm thick, surface treated with hardener.

7 PRODUCTION UPGRADE (OPTIONAL)

Increased façade and roof insulation.

Corrugated steel sheets, mineral wool insulation, PVC membrane.

8 OFFICES

2 level custom designed in-built, incl. offices, socials, locker rooms, day room, cafeteria and kitchen. excl. furniture and appliance

4 FAÇADE

Horizontal sandwich panels with mineral wool insulation.

9 OUTSIDE AREAS

Hard areas from concrete pavers, sloped for drainage.

5 DOCKS

1x electrically operated $3 \times 3.2 \text{ m}$ dock for each 1,000 sq m of hall.



